



HONEY BEST ELEVATOR



AUTOMATIC DOORS



FULL VISION



BIG VISION



SMALL VISION



TELESCOPE SLIDE DOOR

SWING DOOR & COLLESPIBLE GATE



B.V.SWING DOOR



S.V.SWING DOOR



COLLAPSIBLE GATE



IMPERFORATE DOOR

SS & MS CABINS



SS 304 CABIN (MATE)



SS 304 CABIN (DESIGN) MS CABIN (MATE)





MS CABIN (DESIGN)

Quick response **Qualified Engineers Skilled Technicians** +20 Years experience 20+ Employees

Our Strength 2 Years Warranty 1 Year Free Service **CNC Designed Cabins** Latest model LOP/COP Integrated controllers



HONEY BEST ELEVATOR



MOTORS & MRL MOTORS



MONITONARY



SICORE



MRL MONTINARY



SICORE MRL

CONTROLLERS & ARD



HYDRAULIC LIFT



CONTROLLER



V3F DRIVE




ARD BATTERY SYSTEM













make

- Domestic Lifts
- **▼** Commercial Lifts
- Hospital Lifts
- **▼** Apartments Lift
- Goods Lifts
- **▼ Villa Lifts**

- Hydraulic Lifts
- ▼ Machine Room
- Machine roomless
- **▼** Customised Lifts
- 2-30 Person lifts
- ▼ 400-3000 kg lifts

CIVIL DIMENSIONS FOR STANDARD LIFTS

All dimensions in Millimeters

Lift of 1 m.p.s. speed require, Pit depth 1500, Headroom 4250 Lift of 1.5 m.p.s. speed require, Pit depth 1600, Headroom 4800

CENTRE OPENING DOOR LIFT

LO/ Persons	AD Kgs.	SPEED	CAR Width	NSIDE Depth	LIFT \ Width	VELL Depth	Entrance E
6	408	0.6, 1 & 1.5 m/s	1100 1100 1200	1100 1100 900	1400 1550 1750	1400 1550 1450	600 750 850
8	544	0.6, 1 & 1.5 m/s	1000 1000 1300	1400 1300 1100	1700 1700 1900	1800 1800 1900	800 800 800
10	680	0.6, 1 & 1.5 m/s	1400 1300 1300	1250 1350 1350	1800 1800 1900	1800 1900 2100	800 800 800
13	884	0.6, 1 & 1.5 m/s	1100 1100	2000 2000	2000 1900	2500 2500	900 900
16	1088	1 & 1.5 m/s	1300 1300	2000 2000	2100 2100	2500 2500	1000 1000
20	1360	1 & 1.5 m/s	1500 1500	2000 2000	2150 2400	2500 2500	1000 1000
26	1768	1 & 1.5 m/s	2000 2000	1950 1950	2500 2600	2600 2600	1000 2000

Note: BIS recommended car and well size search won in: IS 14665 (Part-I): 2000 (Super ceding IS3534:1979)

SIDE OPENING TELESCOPING DOOR LIFT

LOA Persons	AD Kgs.	SPEED	CAR I Width	NSIDE Depth	LIFT Width	WELL Depth	Entrance E
6	408	0.6, 1 & 1.5 m/s	1100 1100	1000 900	1500 1600	1650 1550	700 700
8	544	0.6, 1 & 1.5 m/s	1200	1200	1600	1850	700
10	680	0.6, 1 & 1.5 m/s	1400	1250	1800	1900	800
13	884	0.6, 1 & 1.5 m/s	1100	2000	1800	2500	1000

Specifications are subjected to change without prior notice.

Photographs, colour swatches and finishes featured are indicative.

Main Branch:

2nd Line, Srinagar Colony, Satyanarayanapuram, VIJAYAWADA.

Branch:

Plot No.6, Block No.B-02, 5th Cross Road, New Autonagar, Kanuru, VIJAYAWADA - 521002.



HONEY BEST ELEVATOR

Email: hnebestelevators@gmail.com